


HEAVY-DUTY SNAP-RING PLIERS

Constructed of thick steel pliers ends and heavy-duty ribbed handles. Includes four pairs of color-coded, precision-ground interchangeable tips: .039" / .99mm and .074" / 1.88mm Straight, .047" / 1.20mm Bent 45° and .047" / 1.20mm Bent 90°. OAL: 7" (18mm)


No.	Style
8845	Internal
8846	External



SNAP-RING PLIERS

Handy pliers with comfortable vinyl handles and four pairs of tips (same sizes as above). OAL: 6" (16cm)

No.	Style
A845	Internal
A846	External
A844	2 Pc. Set (A845 & A846)



A842 5 PC. INTERNAL/EXTERNAL SNAP-RING PLIERS SET

One tool gives full range of snap-ring applications. Includes pliers handle and four tip assemblies (45°, 90° and two straight) to create 8 pliers configurations. Just change position of tip assembly from internal to external. Spring loaded handle with comfort grips. Range: 3/8" - 2" (10mm - 50mm).



8850 CONVERTIBLE SNAP-RING PLIERS

Serves internal rings from 3/8" to 2" (10mm to 48mm) and external rings from 1/4" to 2" (7mm to 48mm). Features "push-buttons" for conversion and thick molded plastic handles. Includes 5 tip sizes: Straight .036" / 90mm, .047" / 1.20mm, .070" / 1.80mm and Bent 90° .036" / 90mm, .047" / 1.20mm, plus hex key. OAL: 7-1/2" (19cm)



SPECIALTY PLIERS




8860 10 PC. FIXED-POINT SNAP-RING PLIERS SET

Service both internal and external Snap-Rings with this set of fixed-point pliers. Each pliers easily converts from internal to external with thumbscrew. Made of heavy-gauge tempered steel and all with vinyl grips. Packed in blow mold case.

Includes the following:

.038" Straight Tip Pliers	.038" 72° Pliers	Straight Pick
.047" Straight Tip Pliers	.047" 72° Pliers	90° Pick
.070" Straight Tip Pliers	.070" 72° Pliers	
.090" Straight Tip Pliers	.090" 72° Pliers	



8870 2 PC. HEAVY-DUTY SNAP-RING PLIERS SET

Repair large equipment with these 16" (40cm) long Internal and External Pliers.

Features spring ratchet lock, 6 pairs of replaceable tips and vinyl handles.


Working range: Internal- 3-1/16" to 6-1/4" (78mm to 159mm) and External-3-1/2" to 6-1/2" (89mm to 165mm). Packed in blow mold case.



8840 LOCK RING PLIERS

Spreads all types of snap rings found on transmissions, brakes, clutch shafts, etc. Spring loaded with single piece forged jaws for extra strength and durability.

Handles are vinyl coated. OAL: 9" (23cm)



A848 HEAVY-DUTY LOCK RING PLIERS

Designed for heavy-duty service on external lock rings used in truck and tractor transmissions. Features spring-loaded handles for extra leverage, vinyl grips for comfort and replaceable tips (includes extra set).

Spread: 3" (75mm). Length 13" (33cm).